Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) An RF module comprising:

a first waveguide <u>having a ground electrode and a line pattern of a conductor</u> for propagating electromagnetic waves in a TEM mode; and

a second waveguide connected to the first waveguide, for propagating electromagnetic waves in another mode different from the TEM mode,

wherein the second waveguide has a region surrounded by at least two ground electrodes facing each other and conductors for bringing the at least two ground electrodes into conduction, wherein the electromagnetic waves in said another mode propagate in the region,

the first waveguide extends in a direction orthogonal to a stacking direction of the ground electrodes of the second waveguide, an end of the first waveguideline pattern of the conductor is directly connected so as to be conductive to one of the ground electrodes of the second waveguide from the direction orthogonal to the stacking direction, and

magnetic fields of the first and second waveguides are coupled in an E plane of the second waveguide so that the direction of the magnetic field of the electromagnetic waves propagated in the first waveguide and the direction of the magnetic field of the electromagnetic waves in another mode propagated in the second waveguide match with each other.

2. (Previously Presented) An RF module according to claim 1, wherein the second waveguide is to propagate the electromagnetic waves in a TE mode.

3. (Currently Amended) An RF module according to claim 1, wherein the first waveguide is positioned between the ground electrodes facing each other in the second waveguide, and

thean end of the line pattern in the first waveguide is conductively connected to one of the ground electrodes facing each other.

4. (Currently Amended) An RF module according to claim 1, wherein the first waveguide has a-the line pattern made of the conductor formed on a dielectric substrate, and substrate.

------a line pattern disposed on the dielectric substrate.

5. (Previously Presented) An RF module according to claim 4, wherein a plurality of penetrating conductors penetrating the dielectric substrate are provided around the line pattern so as to sandwich the line pattern and

an interval between the penetrating conductors sandwiching the line pattern in the width direction is equal to or less than a cut-off frequency of the electromagnetic waves propagating through the first waveguide.

- 6. (Canceled)
- 7. (Original) An RF module according to claim 1, wherein a penetrating conductor for coupling adjustment is provided in a coupling portion between the first and second waveguides.
- 8. (Original) An RF module according to claim 3, wherein a window is provided in at least one of a ground electrode side to which the first waveguide is conductively connected and the side opposite to the ground electrode side in the coupling portion of the first waveguide.
- 9. (Currently Amended) An RF module according to claim 1, wherein the second waveguide has a stacking structure in which three or more ground electrodes are

stacked and has a plurality of propagation regions for the electromagnetic waves in the stacking direction, and

thean end of the <u>line pattern in the</u> first waveguide is conductively connected to the ground electrode between neighboring propagation regions in the second waveguide.

- 10. (Currently Amended) An RF module according to claim 9, wherein anthe end of the line pattern in the first waveguide is conductively connected to athe ground electrode between neighboring propagation regions in the second waveguide so that the electromagnetic waves propagated through the first waveguide are branched and propagated into the plurality of propagation regions in the second waveguide.
- 11. (Original) An RF module according to claim 1, wherein the first waveguide is a strip line, a microstrip line, or a coplanar line.
- 12. (Previously Presented) An RF module according to claim 1, wherein the second waveguide is to propagate the electromagnetic waves in another mode in a multiple mode.

13-14. (Canceled)